

Accudry²

Standardised European tumble dryer

Agents exclusifs
Verson Vlies Courcier Sarl

VVC

ZA des Waffines, 5
Pavé d'Holluin
F-59126 LINSELLES

T : 03.20.46.59.66

F : 03.20.03.17.38

info@vvc.fr

Accudry² is the perfect partner for Wascator, providing you with repeatable and standard conditions for both washing and tumble drying.

This air-vented tumble dryer is used to simulate domestic laundering conditions and is designed to reduce machine and operator variables to the absolute minimum.



Designed With You In Mind

- Guaranteed compliance with standards and retailers' test methods
- Accurate and repeatable control of heating and cooling periods
- Precise control of exhaust air temperature
- Dual filtration system to avoid blockages
- Maintenance and UKAS-accredited calibration service
- Trouble shooting and spare parts support



Standards

EN ISO 6330:2012
EN ISO 6330:2000
Marks & Spencer P1A
Next 7, 7a, 7b, 9, 10, 11, 12, 34 and 36a
The Woolmark Company 31 and 254

Technical Specifications

Width: 600mm
Depth: 625mm
Height: 850mm
Volume: 95l
Capacity: 5kg (dry load)
Exhaust Air Temperature: Up to 80°C*
Rotational Speed: 56rpm
Power: Single phase 220/230V 50Hz (60Hz not available)
Life expectancy: 12000h (subject to annual servicing by James Heal)
*80°C is a maximum figure, which in practice is never likely to be reached