

Verson Vlies Courcier Sarl



## **BA**310 Binocular

The BA310 is designed for the rigors of daily routine work in the demanding applications of Universities, Clinics, Laboratories and any other life science or medical application requiring quality optical performance. This model's full Koehler configuration provides maximum illumination quality for even the most demanding samples. Additional contrast methods and discussion devices, ensure this model will offer long term functionality to all user levels. **Distributeurs** 

			Sector out
Model	BA310 Binocular	VVC.	T : 03.20.46.59.66 F : 03.20.03.17.38
Optical System	Colour Corrected Infinity Optical System (CCIS®)	ZA des Wattines, 5 Pavé d'Halluin	info@vvc.fr
Observation tube	Binocular head, 360° Swiveling	F-59126 LINSELLES	
Interpupillary distance	48-75mm		
Inclination	30° inclined, 360° rotating		
Eyepieces	N-WF10X/20mm with diopter adjustment, +/- 5 diopter		
Nosepiece	Reversed quintuple revolving nosepiece		
<b>Objective classification</b>	Infinity Corrected CCIS EF-N Plan Achromat, DIN		
Objectives	4X/0.10 (WD 6.3mm), 10X/0.25 (WD 4.4mm),		
	40X/0.65/S (WD 0.35mm), 100X/1.25/S-Oil (WD 0.	13mm)	
Objective mounting thread	W 4/5" x 1/36" (RMS standard)		
Stage	Built-in low position coaxial mechnical stage with sample holder		
Stage size	175X140mm		
Mechanical stage X&Y range	76X50mm		
Upper limit stop	Upper limit stop preset but adjustable		
Condenser	Focusable Abbe Condenser N.A. 0.90/1.25 with iris diaphragm and slot for contrast sliders		
Focus mechanism	Coaxial coarse and fine focusing system with tension adjustment		
Fine Focus precision	2 µm minimum increment		
Z-axis movement	20mm		
Filter holder	On top of the illuminator with fixing cap		
Illumination	6V/30W Quartz Halogen Koehler illumination with intensity control		
Transformer	Internal		
Power supply	100-240V (CE)		
Accessories included	Blue filter, immersion oil 5ml, power cord, cord hanger, dustcover, allen key, thumb screw		
	and spare fuse		
Dimensions	400x200x400mm		
Weight	8,6kg		



Add a Moticam camera to capture, document, annotate and share images and videos with the Motic Images Plus 2.0 software.



Distributeurs Verson Vlies Courcier Sarl

T:03.20.46.59.66



## BA210 Trinocular

The BA210 is designed for both educational and teaching environments from basic life sciences to medical applications. Through the Motic Infinity Optics (CCIS®), the BA210 delivers a new higher level of performance in education and training. Contrast methods like Phase Contrast, Polarization and Darkfield are easily performed by using optional accessories.

		<b>T</b> : 03.20.46.59.66 <b>F</b> : 03.20.03.17.38	
Model	BA210 Trinocular	ZA des Wattines, 5 Pavé d'Halluin info@vvc.fr	
Optical System	Colour Corrected Infinity Optical System (CCIS®)	F-59126 LINSELLES	
Observation tube	Trinocular head, Siedentopf type		
Interpupillary distance	55-75mm		
Trinocular light split	100:0/20:80		
Inclination	30° inclined, 360° rotating		
Eyepieces	N-WF10X/20mm with diopter adjustment, +/- 5 diopter		
Nosepiece	Reversed quadruple revolving nosepiece		
<b>Objective classification</b>	Infinity Corrected CCIS EF-N Plan Achromat, DIN		
Objectives	4X/0.10 (WD 6.3mm), 10X/0.25 (WD 4.4mm),		
	40X/0.65/S (WD 0.35mm), 100X/1.25/S-Oil (WD 0.	13mm)	
Objective mounting thread	W 4/5" x 1/36" (RMS standard)		
Stage	Built-in low position coaxial mechnical stage with sample holder		
Stage size	140X135mm		
Mechanical stage X&Y range	76X50mm		
Upper limit stop	Upper limit stop preset but adjustable		
Condenser	Focusable Abbe Condenser N.A. 1.25 with iris diaphragm and slot for contrast sliders		
Focus mechanism	Coaxial coarse and fine focusing system with tension adjustment		
Fine Focus precision	2 µm minimum increment		
Z-axis movement	20mm		
Filter holder	On top of the illuminator with fixing cap		
Illumination	6V/30W Quartz Halogen illumination with intensity control		
Transformer	Internal		
Power supply	100-240V (CE)		
Accessories included	Immersion oil 5ml, power cord, cord hanger, dustcover, allen key, thumb screw and spare fuse		
Dimensions	360x190x398mm		
Weight	7,2kg		



Add a Moticam camera to capture, document, annotate and share images and videos with the Motic Images Plus 2.0 software.